



# Inland 19 ULTRA

## Material Safety Data Sheet

Revision Date January 2007

For Chemical Emergency Call Chemtrec 800-424-9300

- 1. Substance/Company Identification**      PRODUCT NAME:      **Inland 19 ULTRA**  
CAS NUMBER: 8042-47-5  
MANUFACTURER:      Inland Vacuum Industries  
Churchville NY 14428  
(585) 293-3330
- 2. Composition/ Ingredients**      GENERIC NAME:      Hydrotreated technical white  
petroleum oil and additives  
HAZARDOUS INGREDIENTS: None
- 3. Hazards Identification**      POSSIBLE ENTRY ROUTES: Ingestion, inhalation of oil mists  
This product is not classified as hazardous.  
ACUTE EFFECTS: Exposure to oils mists may cause nausea and eye  
irritation. Detailed studies have not been made, but material is not  
expected to be dermatitic or a sensitizer.  
CHRONIC EFFECTS: Unknown.
- 4. First Aid Measures**      SKIN: Wash with soap and water.  
EYES: Flush with water. Contact a physician!  
INGESTION: If swallowed, do not induce vomiting.  
Contact a physician. Small amounts in mouth may be washed out.
- 5. Fire Fighting Measures**      FLASH POINT: >243 C  
METHOD USED: Cleveland Open Cup  
EXPLOSIVE LIMITS LOWER: Unknown UPPER: Unknown  
EXTINGUISHING MEDIA: Water fog, chemical foam or carbon  
dioxide. NFPA Class III B Material.  
SPECIAL FIREFIGHTING PROCEDURES: Wear breathing gear  
when fighting fires in enclosed spaces; incomplete combustion of this  
material produces carbon monoxide!  
UNUSUAL FIRE AND/OR EXPLOSION HAZARDS: None
- 6. Accidental Release Measures**      PROCEDURE TO BE FOLLOWED IN EVENT OF RELEASE: Small  
spills may be wiped up with a rag. Large spills should be picked up  
immediately with an absorbent.
- 7. Handling and Storage**      HANDLING: None known  
STORAGE: None known
- 8. Exposure Controls/Personal Protection**      ENGINEERING CONTROL MEASURES: None required  
RESPIRATORY PROTECTION: See notes on ventilation below.  
PROTECTIVE GLOVES: Yes - made of oil-impermeable rubber  
SAFETY GLASSES/GOGGLES: Yes - glasses should have side shields  
OTHER PROTECTIVE EQUIPMENT: None should be required under  
normal use.
- 9. Physical & Chemical Properties**      PHYSICAL STATE: Liquid  
VAPOR PRESSURE: < .0001 Torr @ 25C

EVAPORATION RATE (ether = 1): Nil  
 VAPOR DENSITY: approximately 14  
 WT % VOLATILES: Nil  
 SPECIFIC GRAVITY: 0.86  
 VISCOSITY: 55 cst @ 40 C  
 SOLUBILITY IN WATER: Nil  
 APPEARANCE: transparent, colorless, viscous liquid with a faint petroleum odor.

**10. Stability & Reactivity**

STABILITY: Material is stable  
 CONDITIONS TO AVOID: Continuous exposure to temperatures > 200 C  
 INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers  
 HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide.

**11. Toxicological Information**

ACUTE ORAL LD50(MG/KG): None known  
 ACUTE DERMAL LD50: None  
 ACUTE INHALATION: US Gov't 8 hr TWA limit for exposure to oil mists is 5 mg per cubic meter

**12. Ecological Information**

ENVIRONMENTAL: When used and/or disposed of as indicated, no adverse  
 MOBILITY: Non-volatile and insoluble in water.  
 DEGRADABILITY: Slowly biodegradable in aerobic conditions.

**13. Disposal Considerations**

Product and packaging must be disposed of in accordance with Federal, State and local regulations. Material may be returned for reclamation.

**14. Transport Classification**

Not classified as hazardous for transport by air, sea or road.

**15. Regulatory Information**

TSCA: This material is in compliance with the TOXIC SUBSTANCE CONTROL ACT (15 USC 2601-2629) and is listed in the TSCA Inventory.

**HAZARD CATEGORIES FOR SARA 311/312 REPORTING**

HEALTH	Immediate (Acute)	No
HEALTH	Delayed (Chronic)	No
PHYSICAL	Fire	No
PHYSICAL	Sudden release of pressure	No
PHYSICAL	Reactive	No
PHYSICAL	Nuisance Mist/ Dust Only	No

01=SARA 313	11=NJRTK	21=TSCA Sect 5(a)(2)
02=MASS RTK	12=CERCLA 302.4	22=TSCA Sect 6
03=NTP Carcinogen	13=MN RTK	23=TSCA Sect 12(b)
04=CA Prop 65-Carcin	14=ACGIM TWA	24=TSCA Sect 8(a)
05=CAProp65-ReprotTox	15=ACGIH STEL	25=TSCA Sect 8(d)
06=IARC Group 1	16=ACGIH Calc TLV	26=TSCA Sect 4(a)
07=IARC Group 2A	17=OSHA PEL	27=Canadian WHMIS
08=IARC Group 2B	18=DOT Marine Pollutant	28=OSHA CEILING
09=SARA 302/304	20=EPA Carcinogen	
10=PA RTK		

The following components of this material are found on the regulatory lists indicated.

DISTILLATES, HYDROTREATED HEAVY PARAFFINIC  
 Is found on lists: 14,15,17

NEW JERSEY RTK CLASSIFICATION:  
 Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et.seq., the product is to be identified as follows:

PETROLEUM OIL

**16. Other Information**

**NFPA RATING**

FLAMMABILITY	1
HEALTH HAZARD	1
REACTIVITY	0
SPECIAL HAZARD	NONE